

	DefensePro 6	DefensePro 20	DefensePro 60	DefensePro 110/220	DefensePro 200/400
PERFORMANCE					
On-Demand Scalable Throughput Licenses	DP model 6-02 - 200 Mbps DP model 6-05 - 500 Mbps DP model 6-1 - 1 Gbps DP model 6-2 - 2 Gbps DP model 6-3 - 3 Gbps DP model 6-5 - 5 Gbps	DP model 20-2 - 2 Gbps DP model 20-4 - 4 Gbps DP model 20-8 - 8 Gbps DP model 20-12 - 12 Gbps	DP model 60-10 - 10 Gbps DP model 60-20 - 20 Gbps DP model 60-40 - 40 Gbps	DP model 110-40 - 40 Gbps/ DP model 220-120 - 120 Gbps	DP model 200-80 - 80 Gbps/ DP model 400-160 - 160 Gbps
Max Mitigation Capacity/Throughput	6 Gbps	20 Gbps	60 Gbps	110 Gbps/220 Gbps	200 Gbps/400 Gbps
Max Legit Concurrent Sessions	3,000,000	12,000,000	12,000,000	22,000,000	72,000,000
Max Attack Concurrent Sessions	Unlimited				
Max DDoS Flood Attack Prevention Rate	5,800,000 pps	25,000,000 pps	25,000,000 pps	50,000,000 pps/146,000,000 pps	330,000,000 pps
SSL/TLS Connections per Second	20KCPS (RSA 2K)	95KCPS (RSA 2K)	95KCPS (RSA 2K)	150KCPS (RSA 2K)	-
Latency	< 60 microseconds				
Real-Time Signatures	Detect attacks and protect in less than 18 seconds				
INSPECTION PORTS					
10/100/1000 Copper Ethernet	6	-	-	-	-
1 GE/10 GE	2 (SFP+)	24 (SFP+)	24 (SFP+)	24 (SFP+)	20 (SFP+)
40 GE	-	-	-	4 (QSFP+)	4 (QSFP+)
100 GE	-	-	-	4 (QSFP28)	4 (QSFP28)
MANAGEMENT PORTS					
10/100/1000 Copper Ethernet	2				
Management Console	RJ-45				
OPERATION MODE					
Network Operation	Transparent L2 Forwarding/IP Forwarding				
Deployment Modes	Inline; SPAN port monitoring; Copy port monitoring; Out-of-path mitigation (scrubbing center solution)				
Tunneling Protocols	VLAN Tagging, L2TP, MPLS, GRE, GTP, IPinIP				
IPv6	Yes				
Jumbo Frame	-	Supported			
Block Actions	Drop packet, reset (source, destination, both), suspend (source IP address, source port, destination IP address, destination port or any combination), challenge-response for TCP, HTTP and DNS suspicious traffic			Drop packet, reset (source, destination, both), suspend (source IP address, source port, destination IP address, destination port or any combination), challenge-response for TCP, HTTP and DNS suspicious traffic	
HIGH AVAILABILITY					
Fail-open/fail-close ¹	Internal fail-open/fail-close for integrated copper ports; Internal fail-close for fiber ports or optical transceivers (i.e., SFP+)	Internal fail-close for optical transceivers (i.e., SFP+)		Internal fail-close for optical transceivers (e.g., SFP+, QSFP28, QSFP+, QSFP28)	Internal fail-close for optical transceivers (e.g., SFP+, QSFP, QSFP28)
Dual Power Supply	Yes, hot swappable				
PHYSICAL					
Dimensions (W x D x H) mm	436 x 406 x 44 mm (1U) EIA Rack or Stand-alone: 482 mm (19 in)	436 x 480 x 88 mm (2U)	436 x 480 x 88 mm (2U)	482 x 550 x 87 mm (2U) EIA Rack or Stand-alone: 482 mm (19 in)	424 x 600 x 88 mm (2U) EIA Rack or Stand-alone: 482 mm (19 in)
Weight	Single power supply: 6 kg (13.2 lbs) Dual power supply: 7 kg (15.4 lbs)	11.2 kg (24.7 lbs)	11.2 kg (24.7 lbs)	14.5 kg (31.9 lbs)	18.7 kg (41.2 lbs)
Power Supply (Auto-range)	AC:100-120V/200-240V, 47-63 Hz DC: -36 to -72V	AC:100-120V/200-240V, 47-63 Hz DC: -36 to -72V	AC:100-120V/200-240V, 47-63 Hz DC: -36 to -72V	AC:100-120V/200-240V, 47-63 Hz DC: -36 to -72V 80 plus certified	AC:100-120V/200-240V, 47-63 Hz DC: -36 to -72V
Power Consumption	140W	Dual PS: 320W		550W	890W
Heat Dissipation	480 BTU/h	Dual PS: 1,088 BTU/h		1,880 BTU/h	2,930 BTU/h
Operating Temperature	0°-40°C (32°-104°F)				
Humidity	5% to 95% (non-condensing)				
ENVIRONMENTAL SPECIFICATIONS					
Compliance & Certifications					
Compliance					
RoHS	Compliant (EU directive 2011/65/EU, 2015/863/EU)				
Safety/EMC/EMI	FCC Part 15, Class A; IC ICES-003; UL 60950-1:2007 R12.11; CAN/CSA-C22.2 No. 60950-1-07+A1:2011; EN 60950-1:2006+A1:2009+A1:2010+A12:2011+A2:2013; IEC 60950-1:2005 (Second Edition)+Am 1:2009+Am 2:2013; EN 60950-1:2006+A11:2009; AS/NZS 60950.1:2015	FCC Part 15, Class A; IC ICES-003; UL 60950-1:2007 R10.14; CAN/CSA-C22.2 No. 60950-1-07+A1:2011+A2:2014; EN 55022:2010/AC:2011 Class A; EN 61000-3-2:2014; EN 61000-3-3:2013; EN 55024:2010; IEC 61000-4-2:2008; IEC 61000-4-3:2006+A1:2007; IEC 61000-4-4:2012; IEC 61000-4-5:2014; IEC 61000-4-6:2013; IEC 61000-4-8:2009; IEC 61000-4-11:2004; IEC 61000-4-12:2006; IEC 60950-1:2005 (Second Edition)+Am 1:2009+Am 2:2013; EN 60950-1:2006+A11:2009+A12:2011+A2:2013; NEBS	FCC Part 15, Subpart B, Class A; IC ICES-003:2016 Issue 6, Class A; ANSI C63.4:2014; UL 60950-1:2007 R10.14; CAN/CSA-C22.2 No. 60950-1-07+A1:2011+A2:2014; UL 62368-1:2007 R10.14; CAN/CSA-C22.2 No. 62368-1-14; EN 55024:2010; EN 55032:2015 +AC:2016/ CISPR 32:2015 +COR1:2016/ AS/NZS CISPR 32:2015, Class A; EN 300 386 V2.1.1 (2016-07); EN 61000-3-2:2014; EN 61000-3-3:2013; EN 61000-4-2:2009; EN 61000-4-3:2006 +A1:2008 +A2:2010; EN 61000-4-4:2012; EN 61000-4-5:2014; EN 61000-4-6:2014; EN 61000-4-8:2014; EN 61000-4-11:2004	FCC Part 15B (Class A); ANSI C63.4:2014; CISPR 32:2012/2015, Class A; AS/NZS CISPR 32:2013/2015, Class A; IEC 60950-1:2005/AMD1:2009; IEC 60950-1:2005/AMD2:2013; IEC 60950-1:2005; EN 60950-1:2006/A11: 2009/A1:2010/A12:2011/A2:2013; AS/NZS 60950.1:2015; IEC 62368-1:2014; EN 62368-1:2014/A11:2017; AS/NZS 62368.1:2018; EN 300 386 V2.1.1 (2016-07), Class A; EN 55032:2015 +AC:2016; EN 61000-3-2:2014, Class A; EN 61000-3-3:2013; EN 61000-4-2:2009; EN 61000-4-3:2006 +A1:2008 +A2:2010; EN 61000-4-4:2012; EN 61000-4-5:2014; EN 61000-4-6:2014; EN 61000-4-8:2014; EN 61000-4-11:2004	FCC Part 15B (Class A); ANSI C63.4:2014; CISPR 32:2012/2015, Class A; AS/NZS CISPR 32:2013/2015, Class A; IEC 60950-1:2005/AMD1:2009; IEC 60950-1:2005/AMD2:2013; IEC 60950-1:2005; EN 60950-1:2006/A11: 2009/A1:2010/A12:2011/A2:2013; AS/NZS 60950.1:2015; IEC 62368-1:2014; EN 62368-1:2014/A11:2017; AS/NZS 62368.1:2018; EN 300 386 V2.1.1 (2016-07), Class A; EN 55032:2015 +AC:2016; EN 61000-3-2:2014, Class A; EN 61000-3-3:2013; EN 61000-4-2:2009; EN 61000-4-3:2006 +A1:2008 +A2:2010; EN 61000-4-4:2012; EN 61000-4-5:2014; EN 61000-4-6:2014; EN 61000-4-8:2014; EN 61000-4-11:2004
Certifications	CCC (China), TUV (U.S., Canada), CE (Europe), FCC (U.S.), KCC (Korea), BSMI (Taiwan), EAC (Russia), VCCI (Japan), Anatel (Brazil), SDPPI (Indonesia)	CCC (China), TUV (U.S., Canada), CE (Europe), FCC (U.S.), KCC (Korea), BSMI (Taiwan), EAC (Russia), VCCI (Japan), Anatel (Brazil), SDPPI (Indonesia)	CCC (China), TUV (U.S., Canada), CE (Europe), FCC (U.S.), KCC (Korea), BSMI (Taiwan), EAC (Russia), VCCI (Japan), Anatel (Brazil)	CCC (China), TUV (U.S., Canada), CE (Europe), FCC (U.S.), KCC (Korea), BSMI (Taiwan), EAC (Russia), VCCI (Japan), Anatel (Brazil)	CCC (China), UL (U.S., Canada), CE (Europe), FCC (U.S.), KCC (Korea), EAC (Russia), VCCI (Japan), Anatel (Brazil)
Warranty	1-year hardware and software maintenance				
Support	Certainty Support Program				

¹ External fiber fail-open switch is available at additional cost.

DefensePro VA	
Hypervisor	KVM kernel 3.19, QEMU 2.0, VMware (ESX server versions: 5.1, 5.5, 6.0)
Minimum VM requirements	2 vCPUs, 8GB RAM, 10GB storage
PERFORMANCE¹	
OnDemand Scalable Throughput Licenses	DefensePro VA 200 Mbps, 500 Mbps, 1 Gbps, 2 Gbps, 5 Gbps, 10 Gbps, 20 Gbps ²
Max Mitigation Capacity/Throughput	20 Gbps per DefensePro VA ²
Max Legit Concurrent Sessions	1,000,000 sessions per vCPU
Max Attack Concurrent Sessions	Unlimited
Max DDoS Flood Attack Prevention Rate	Up to 950 KPPS per vCPU
Latency	< 60 microseconds
Real-Time Signatures	Detect attacks and protect in less than 18 seconds
INSPECTION PORTS	
10 GE	2 (Intel® Ethernet Server Adapter X520, 10 GbE; Intel® Ethernet Controller XL710, 40 GbE)
MANAGEMENT PORTS	
Ethernet	Via Virtual interface (virtio)
Management Console	KVM Virsh; VMware Serial Port
OPERATION MODE	
Network Operation	Transparent L2 Forwarding
Deployment Modes	In-line
Tunneling Protocols	VLAN Tagging, L2TP, MPLS, GRE, GTP, IPinIP
IPv6	Yes
Jumbo Frame	Up to 2KB
Block Actions	Drop packet, Challenge-Response for TCP, HTTP and DNS suspicious traffic
HIGH AVAILABILITY	
Fail-open/fail-close	N/A
Advanced Internal Overload Mechanism	N/A
Active-Passive Cluster	N/A
Warranty	Standard warranty for 90 days
Support	Certainty Support Program

¹ Performance figures assume Intel server-grade processor with 3 GHz

² 20Gbps Throughput License supported on KVM

This document is provided for information purposes only. This document is not warranted to be error-free, nor subject to any other warranties or conditions, whether expressed orally or implied in law. Radware specifically disclaims any liability with respect to this document and no contractual obligations are formed either directly or indirectly by this document. The technologies, functionalities, services, or processes described herein are subject to change without notice.

© 2019 Radware Ltd. All rights reserved. The Radware products and solutions mentioned in this document are protected by trademarks, patents and pending patent applications of Radware in the U.S. and other countries. For more details, please see: <https://www.radware.com/LegalNotice/>. All other trademarks and names are property of their respective owners.